

Adjustable Lowering Link Installation Instructions

Installation Guidelines & Safety

You Must Follow and Understand these Instruction

1. Important Notice

It is the responsibility of the purchaser to follow all instruction and or guidelines and safety precautions detailed in the kit instructions and other manufactures products used with and within this kit. It is your responsibility to determine the compatibility of this part or devices in this part with the vehicle and other components. SpencerCycle.com assumes no responsibility or liability for damages incurred from the use of products or parts of products sold or manufactured by SpencerCycle.com on motor vehicles used for or in competition racing events. SpencerCycle.com does not recommend or approve of products or use of products manufactured by SpencerCycle.com or sold by SpencerCycle.com to be used on motor vehicles on which are or may be operated on public highways or roads, and SpencerCycle.com assumes absolutely no responsibility for damages arising or incurred from such use. SpencerCycle.com does not promote or intend its products, manufactured or sold by SpencerCycle.com to be use for illegal street racing. It is the purchasers responsibility to check and abide by all state and local laws pertaining to the use of aftermarket products.

2. Installation

It is basically a simple unbolt and bolt up process. You will need to remove the stock lowering links by first supporting motorcycle so that is steady and will not fall over and injure anyone. The rear of the motorcycle must be off the ground. Remove the rear wheel and exhaust if needed to gain access to the links. Remove the stock links and replace with the units you have purchased. The recess points outward and the flat sides fit against the shock pivot and swing arm pivot. Tighten all bolt to factory specs and or refer to the factory service manual for further instructions or call us if you have additional questions. Once installed make a mark with a marker on one side of both links...so you will know how many times to turn each side in order to get the load even. **WARNING!** This is a critical measurement and must be exact. Uneven load stress can cause failure and you must equalize the load by turning each link the same from point to point or failure of the link may happen. Once you have the desired height you need check to make sure you still have at least .500 (1/2) thread still inside the main threaded body. **WARNING!** This must be kept at all times (when extending the links out to the furthest end on both threaded male gold end on both links) Failure of the product will happen if you do not maintain a minimum .500" (1/2 inch) of threads in the main link body. We recommend you have a qualified professional shop install this product. If you have purchased part number SP-1902FA14 and or SP-1902FASS14 there is a additional installation sheet drawing included to aid you in the installation of those products, as these products have parts unique to the models they fit. As always if you have question please contact us before installation of anykind.

3. Warranty

SpencerCycle.com warrants to the original purchaser that the components shall be free from defects in parts and workmanship under normal use for 90 days from date of purchase. This warranty is limited to the repair or replacement of any component found to be defective when returned to SpencerCycle.com. The items must be accomplice with original date of purchase and a copy of original invoice or the warranty will be void. This warranty does not apply to any component that has be installed incorrectly installed or misused, repaired, tampered with by misuse, negligence or by accident.

4. Liability Release and Disclaimer

Spencer Cycle Center Inc. Assumes NO LIABILITY for damages incurred by the purchaser, in the use of products manufactured by and for Spencer Cycle Center Inc. The PURCHASER ASSUMES ALL LIABILITY ABD RESPONSIBILITY for attaching and or installation and maintaining any product manufactured by or for Spencer Cycle Center Inc. The purchaser understands that any alteration or modification to a motorcycle or motor vehicle may increase the risk of personal injury, death, or an accident. Installation of this product means the purchaser has read, understand and accepts ALL LIABILITY for using this product. The purchaser releases the parts manufacturer, and Spencer Cycle Inc. from all liabilities pertaining to the installation and use of purchased parts. Chroming, sanding, grinding or any alteration to the product in any way other than the way it is supplied to you voids all warranty. visit www.spencercycle.com for more info.

Thank You for Purchasing you parts from Spencer Cycle Center Inc. if you have any concerns or question please contact us. Toll Free 1-800-510-1945 Mon-Fri 9-6 est.