

# K & P Lifetime Oil Filter

## Installation - Spirol Lokstyle

After all components are clean and dry, place the filter element back in the case making sure the three "ears" on the element fall into their slots in the case. Next, reference the spirol lok installation below. (Note: The top (upper) ring of the spirol lok has a bent tip.)



1

Hold the bottom (lower) spirol lok ring in your right hand with the bottom end to your left.



4

Continue this technique until the spirol lok is completely installed into the slot in the housing.



2

Insert the very bottom END of the spirol lok into the slot in the housing.



5

The filter element will normally be a little loose in the housing. As the filter tightens on the engine it will tighten against the spirol lok which will eliminate any play.



3

With your right thumb on the top side of that bottom ring and your forefinger under that bottom ring, tip the top of the spirol lok toward you (like a cup of coffee) while pushing the spirol lok down into the slot in the housing. Do not try to thread or spin the spirol lok in, the key is the tipping motion of your right hand while pushing down to get it to snap in.

*(Click on image for larger picture)*

**Motorcycle Performance Specialties**  
380 Orange Lane - Casselberry, Florida 32707  
Phone: (321) 972-8282 - Fax: (321) 972-5123  
Hours: 9am - 5pm, Monday - Friday  
Sales E-Mail: [sales@mpsracing.com](mailto:sales@mpsracing.com)

Double check and/or reinstall the rubber quad-ring (either side up). Lube the quad ring surface with a thin film of clean oil and install filter on the bike. The filter should spin on at least 3 full turns. Torque the filter to 20-25 ft lbs and recheck torque after 100 miles.

**Cleaning:** We recommend the K&P Micronic Stainless Steel Oil Filter be cleaned frequently when first purchased or when engine work has been performed. This will give you a feel for how much debris is being filtered out of your machines oil and help you decide how often you want to clean the filter for your application. At minimum, clean the filter with every oil change. Remember, oil is the lifeblood of your machine, keep it clean!

Wash the reusable stainless steel filter element in clean solvent, kerosene, aerosol carburetor cleaner or any other degreasing agent; even common dish soap and water. If inspection of trapped debris is desired, flush the particles into a light colored, clean container. Once clean, lightly blow air through the filter from the inside out to remove any small particles or cleaning agent from the screen. Finally, if you have a spin on model, clean the inside of the filter housing using the same type of cleaner as used on the reusable filter element.

**Motorcycle Performance Specialties**

380 Orange Lane - Casselberry, Florida 32707

Phone: (321) 972-8282 - Fax: (321) 972-5123

Hours: 9am - 5pm, Monday - Friday

Sales E-Mail: [sales@mpsracing.com](mailto:sales@mpsracing.com)