

MPS Command Center

The MPS Command Center is designed to provide a versatile workstation for your laptop computer. Please read the mounting instructions before using your Command Center for the first time. It is important to routinely check the tightness of all fasteners. Knurled thumbscrews are installed on the set screws for easy tightening. The set screws must engage the dimples in the ½" crossbar to ensure a steady platform. Remove the protective sheet from the tray before installation.

Insure proper mounting for safe operation. Do not use the Command Center while operating your motorcycle.

MPS is not responsible for any damage caused while using the Command Center.

Loctite has been used on the fasteners securing the mounting pegs. All stainless steel fasteners accept a 1/8" allen wrench and are 10-24 thread.

Before mounting the Command Center, consider its many positions. It can be extended to the left or right, forwards or backwards. The tray will sit differently if your motorcycle is parked with the factory side stand, a rear stand or a front wheel chock. Consider how your motorcycle is most often parked before mounting the Command Center.

Mounting –

1. Assemble the main block to the mounting base.
2. Click the base of the Command Center into the female rear seat receptacle of your motorcycle. Be sure both pegs are secure.
3. Insert the end of the ½" crossbar with two dimples into the main block. Tighten the set screw into either of the two dimples. One of these dimples lines up with the 8 dimples on the other end of the crossbar and the second dimple is half way between. Always pay attention to the depth of the set screw, this will indicate if you engaged the dimple.
4. Slide the smaller tray mounting block onto the crossbar. Do not tighten the set screw.
5. Slide the larger tray mounting block onto the crossbar. Tighten the set screw. If there is not a dimple in a good position, use the second dimple on the end that is in the main base.
6. Secure the tray to the mounting blocks using the supplied fasteners. Tighten the set screw on the supporting block.

If you have any more questions we have a Frequently Asked Questions page at our web site as well as the telephone tech support. Thank you for your purchase of this MPS product. All products sold by MPS are for use at closed course competition events and not for use on public streets or highways.