

MPS LED Shift Light Bulb For Dyna Shift Lights



- 1) Unplug your shift light's 2 pin connector from the shift minder.
- 2) On the shift light's 2 pin connector locate the small tangs on the male pin connectors. These are toward the base of the connector. Using a small scribe push them in, releasing the pin connector. You can skip this and cut the connector off instead if you like.
- 3) Remove the single 4-40 screw that holds the lens portion of your shift light in place.
- 4) Remove the lens portion of your shift light.
- 5) Pull the old bulb and socket assembly out of the lens portion.
- 6) Snap the new LED Conversion in place.
- 7) Route the wires out the hole in the back of the shift light housing.
- 8) Replace the 4-40 screw that holds the shift light lens in place.
- 9) Plug the bare plastic 2 pin connector housing from the LED kit into the shift minder 2 pin connector.
- 10) Push the red wire's pin connector into the 2 pin plastic connector. It must be matched with the brown (positive) wire from the shift minder. Repeat the process with the black wire's pin connector. It must be matched with the white (negative) wire from the shift minder.
- 11) Congratulations, you have installed your LED Conversion.

If you have any more questions we have a Frequently Asked Questions page at our web site as well as the telephone tech support. Thank you for your purchase of this MPS product. All products sold by MPS are for use at closed course competition events and not for use on public streets or highways.