

Installation instructions for the TT-13B Tiger Tail Inner fender
READ BEFORE WORKING !!! at least once.

1. Remove rear cowling assembly.
2. Remove battery – ECU – Tool kit and Tank lift arm from plastic inner fender
3. Remove bolt securing starter relay bracket.
4. Remove tip over sensor from rubber mount grommet **(you have to re-install this sensor relay in the same position)**
5. Remove all electrical harness ty-wraps and securing plastic clamps. **(remember where everything went...see# 14)**
6. Remove lower sub frame attachment bolts from frame
7. **Loosen** upper sub frame attachment bolts from frame **(do not remove)**
8. Remove foot peg bracket bolts from sub frame on both sides **(let exhaust hang)**
9. Remove 4 shoulder headed bolts from plastic inner fender and remove.

Now you should look like this.



10. Insert your new Tiger Tail inner fender as shown. It's kind of a Houdini insert and twist.





11. Now attach the inner fender to the sub frame as shown with the 2 front shouldered mount bolts.



12. Tweak the tail plate so that it installs under the rear sub frame mounting brace as shown.





13. You may now attach your TST-13B License plate bracket at this time (**if you purchased one**) as shown.



14. You should now make sure your electrical harness is configured correctly and going to the right places. Don't forget your tip over sensor (**proper side up**)
15. Re-install all mount bolts to the sub frame including exhaust hanger/foot peg brackets.
16. Re-install rear cowling, battery, ecu and **hump release cable**.

You should be about done.!